

Form 7.2-1-6 Rev 01

CJ Socket AK Test Socket by Measurement

Date: Date Required: P.O. Number: Ship CJ Sail to: Friddle's or Customer's Address Ship To Address:			
Shipping Method: GROUND NEX Customer Name: (Bill to):	T DAY AIR 2 DAY 3 DAY Patient Name: Sex: Height:		
Contact: Phone:	Weight: Age:		
MEASURE IN MILLIMETERS, PLEASE	Measurements Taken By:		
450	FRIDDLE'S Page 1 of 2		



CJ Socket AK Test Socket by Measurement

CJ Sail Options

Patient Name / Reference Number:

		510117	Internal use only	
	LEFT	RIGHT	Serial #	
Material Color:	Black Coyote (Brown)	Heavy Duty Fabric (Black Only)	Date in	
Closure Options: Standard (1:1) Closure, 1.5" Velcro Attached to Batten		Date Out		
		tten. (Customer supplies Velcro Straps)	TFB	
(2:1) Closure, 1" Loops Attached to Batten, 1" Pressure Buckles with Dacron Strap (No Velcro)				
Other Options:		Residual Limbs, Degrees of Socket Flexion	_ (Required)	
Darts Sewn into Sail (for Irregular Shaped Residual Limbs) Dart Measurements (H" x W"):				
H	OPEN FLAP Design - Medial Side of Sa CJ Socket to Make Dacron-Backed Velc	ail Will Not Have Attachment Holes - Friddle's to Add 1" H	ook Velcro Inside Socket	
Special Instructions:		io Suaps		



Email or Fax completed form to c-fab@friddles.com or 864.369.1149