



# Transfemoral Sail Measurement Form

## CJ Socket Technologies

100 Cummings Center • Suite 207H • Beverly, MA 01915

Tel: 978-922-0413 • Fax: 978-922-0277

[CJSocket@gmail.com](mailto:CJSocket@gmail.com) • [www.CJSocket.com](http://www.CJSocket.com)

Company Name: \_\_\_\_\_

Prosthetist Name: \_\_\_\_\_

Purchase Order #: \_\_\_\_\_ Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Email: \_\_\_\_\_

Shipping Address: \_\_\_\_\_

City: \_\_\_\_\_ State: \_\_\_\_\_ ZIP code: \_\_\_\_\_

Billing Address (if different): \_\_\_\_\_

City: \_\_\_\_\_ State: \_\_\_\_\_ ZIP code: \_\_\_\_\_

Shipping:  Priority Mail 2-3 Day (Standard)  Next Day  Other: \_\_\_\_\_

Patient Height: \_\_\_\_\_, Patient Weight: \_\_\_\_\_, Amputated Side: Left  Right

K Level: 1 2 3 4

Material Color:  Black  Coyote (Brown)  Heavy Duty Fabric (Black Only)

Closure Options:  Standard (1:1) Closure, 1.5" Velcro Attached to Batten  
 (2:1) Closure, 1.5" Loops Attached to Batten. **(Customer supplies Velcro Straps)\*\***  
 (2:1) Closure, 1" Loops Attached to Batten, 1" Pressure Buckles with Dacron Strap (No Velcro)

Other Options:  Proximal Arc (for very Conical or Flexed Residual Limbs, Degrees of Socket Flexion \_\_\_\_\_ (Required)  
 Darts Sewn into Sail (for Irregular Shaped Residual Limbs) Dart Measurements (H" x W"): \_\_\_\_\_  
 This is a Replacement Sail for and existing socket, No Holes Needed  
 OPEN FLAP Design – Medial Side of Sail Will Not Have Attachment Holes – Secured by Closure Choice Above  
 \*\*CJ Socket to Make Dacron-backed Velcro Straps (to be used with (2:1) Closure, 1.5" Loops Attached to Batten)

Special Instructions: \_\_\_\_\_

**Internal use only**

Serial # \_\_\_\_\_

Date in \_\_\_\_\_

Date out \_\_\_\_\_

TFB \_\_\_\_\_

All Measurements from **POSTERIOR Side Only**

Measurements is:  
 Inches  
 CM

Indicate: Medial or Lateral

Indicate: Medial or Lateral

